

Luminous In Brief

Luminous is the most trusted brand in Home
UPS and Inverter Batteries in India. With more
than 2 decades of expertise in Home UPS and
more than 1 decade of expertise in Inverter
Batteries, Luminous at present is among
the leading players in the market with
7 manufacturing units, more than 28 sales
offices in India and presence in over
36 countries. Our 6000 employees serve
more than 60,000 channel partners and
millions of customers. Our motto is Customer
Delight through Innovation & Passion with
focus on execution & team-work.

More than 27 years of history

SUCCESS



2010

Sachin Tendulkar appointed as Brand Ambassador

2011

Luminous -Schneider joint venture

2012

MNRE:CRISIL Recognition

Awarded Consumer Superbrand status in the Inverter Battery category

2013

Won Best Power Back-up Solution Provider Company Award conducted by VAR India

Got ISO 50001:2001 rating

2014

Luminous given Most Trusted Brand status

Luminous joins hands with TERI

2015

Awarded Superbrand Status in the Inverter Battery category again

EXECUTION



2000

First Luminous product got exported

2004

Tie-up for battery technology with Eagle Pitcher Inc. USA

First battery manufacturing plant came into existence

2006

Tie-up with Hyundai, formation of Hyundai Power Products

2007

First manufacturing facility out of India (Lang Ming, China)

Got industry leadership award from Frost & Sullivan



1988 Company was

founded


1991

Manufactured first inverter

PREPARATION

1994

Manufactured first UPS





Vision

Passionately innovate to make life comfortable and efficient.



Mission

Be the brand of choice for products and services that generate, control, store and use electricity efficiently. Through passionate people we innovate to consistently deliver a tangible competitive advantage in reliability, service and cost.



Values

Customer Delight through Innovation & Passion with focus on Execution & Team-work.



Home UPS



Luminous, a leader in Home UPS category has been consistently delivering world-class products that are preferred not only in India but, globally as well for over 2 decades. Luminous Home UPS are manufactured using latest state-of-the-art technology at a highly automated plant in Himachal Pradesh. Our credential lies in satisfaction of over 8 million customers. Luminous has a wide range of Home UPS models meeting diverse needs of the customers.

Inverter Battery



Luminous offers wide range of Inverter Batteries, ranging from 60 Ah to 220 Ah. We have back-up solutions for all kinds of customer requirement ranging from 30 minutes to 12 hours. These batteries are designed smartly to give longer back-up and needs lower maintenance.

Awards & Recognition

| Fig. 5 5 7 6 5 0 1 1 1 V A S Avarded by Frest & Sullivan for Leadership in the Asia Pacific Region | Market Penetration Leadership Award: Received "Frost & Sullivan Market Penetration Leadership Award in Asia Pacific for DC-AC Inverters in non-renewable energy markets" |
|---|---|
| Quality Brands | Quality Brands Award, 2012 to 2014 & Rashtriya Udyog Ratna Award 2014: "Awarded to Luminous based on industrial field survey by National Organization for Commerce & Industry" |
| ACHIEVERS AWARDS | SME Channel Connect & Achievers Awards 2012: Received in 'Best Home UPS' & 'Best Inverter Battery' Categories. |
| Just | Juxt Award: Luminous has also been recognised as the most preferred Inverter/UPS brand for the year 2013/14 by Juxt India online study. |
| VAR India | Best Power Back-up Solution Provider Company: Awarded to Luminous based on the study conducted by VAR India - a leading publication house. |
| | Luminous Brand Award: Winner of "Consumer World Award" for consecutive four years in the inverter category in India. |
| SELECTED SELECTED | Consumer Superbrand: Winner of "Consumer Superbrand" status in the Inverter and Inverter Battery category for the year 2011-12 & again for the same in year 2014-15. |
| WHOTE CRID LIBERTY COLD IS | MNRE CRISIL: Solar Grading: Luminous has been awarded with the MNRE CRISIL SP 1A Grade for its capability as a system integrator in the Photovoltaic segment. |
| Power of Trust | India's most Trusted Brand - 2014 & 2016: Luminous has been again listed as India's most Trusted brand in the category of Power Products in 'The Brand Trust Report, India Study, 2016' which has been recently launched in India). |
| | India's most Attractive Brand 2015: Luminous has been listed as India's most attractive brand in Inverter & Battery category by TRA (formerly Trust Research Advisory). |

Luminous Service



LUMINOUS CARE
DEST SAUTHN DEPLATING SUPPORT
1600 103 1039 1160 500 3039
CAP GLATINOUST dis. 201

100% isPaperlessh Warrantyijysl ok<mark>laV</mark>

Register your Luminous product and enjoy hassle free warranty services. vius ywfeul izksMDV dks jftLVj djok,a vkSj vkuan ys ijs'kkuh eqD okjaVh Isokvksa dk

To Register iftLVj djus ds fy, 1800 103 3039 or 'k

www.luminousindia.com



Onsite service facility



Mobile Application for call login



Online Call Resolution



Direct service from trained professionals



24x7 Call login facility at centralised call center



1200+ Field Service Personnel servicing 3800+ locations pan India



1800 103 3039 I 1860 500 3939 care@luminousindia.com



Network of 100 Company Service Centers and 190 Authorised Service Points

Other Product Offerings





Home Electrical

Products

Online & Line Interactive UPS System







Freedom from power cuts with Luminous Home UPS







Electra Sine is a pure sine wave Home UPS with MCB Protection. The low harmonic distortion makes the Home UPS practically noiseless and the pure sine wave output makes it highly efficient and helps save on electricity bills.

Key Features

- · Rugged technology design for high performance and longer back-up time, specially suited for Indian power conditions
- · Auto holiday mode preserves battery charge and safeguards battery life
- Supports a wide range of batteries with 3-step charging current and 4-step battery type selection
- · Adaptive battery charging control technology (ABCC) ensures faster battery charging and enhances battery life up to 70%



Pure sine wave output



24 months warranty



Supports flat, tubular, SMF & local battery



MCB protection



Overload protection with auto reset



High efficiency

| Model | Electra Sine 865 | Electra Sine 1065 |
|--------------------------------------|---|--|
| Capacity | 700VA | 900VA |
| Input | | |
| Voltage Output | 100-290V | 100-290V |
| Max. Bulb Load Battery | 600 Watt | 720 Watt |
| Maximum Charging Current Physical | 14A | 17A |
| Gross Weight (Kg.) | 9.2 | 10.8 |
| Dimension LxWxH (cm) | 29.2x27.5x12 | 29.2x27.5x12 |
| Protection | Overload, Short-circuit, Battery Deep Discharge & E | Battery Reverse Polarity, MCB Protection |



Electra Square series is yet another top selling Home UPS series of Luminous. It is built with advanced PCB programming, microprocessor and FSW transformer, making it highly efficient. Also, it does not create any humming noise, consumes less power and is capable of taking higher load.

Key Features

- Rugged technology design for high performance and longer back-up time, specially suited for Indian power conditions
- · Auto holiday mode preserves battery charge and safeguards battery life
- Supports a wide range of batteries with 3-step charging current and 4-step battery type selection
- · Adaptive battery charging control technology (ABCC) ensures faster battery charging and enhances battery life up to 70%



| Electra Sq. 665i | Electra Sq. 765 | Electra Sq. 865+ | Electra Sq. 965 El | ectra Sq. 1065 Elect | ra Sq. 1665 |
|------------------|---|---|---|---|--|
| 600VA | 700VA | 800VA | 900VA | 900VA | 1500VA |
| | | | | | |
| 100-290V | 100-290V | 100-290V | 100-290V | 100-290V | 100-290V |
| 540 Watt | 600 Watt | 680 Watt | 700 Watt | 740 Watt | 1350 Watt |
| 13A | 14A | 14A | 17A | 17A | 17A |
| 8.0 | 8.8 | 9.5 | 10.2 | 10.2 | 14.9 |
| 30x21.9x11.5 | 27.5x26.2x12 | 27.5x26.2x12 | 27.5x26.2x12 | 27.5x26.2x12 | 27.5x35.5x14 |
| | 600VA 100-290V 540 Watt 13A 8.0 | 600VA 700VA 100-290V 100-290V 540 Watt 600 Watt 13A 14A 8.0 8.8 | 600VA 700VA 800VA 100-290V 100-290V 100-290V 540 Watt 600 Watt 680 Watt 13A 14A 14A 8.0 8.8 9.5 | 600VA 700VA 800VA 900VA 100-290V 100-290V 100-290V 540 Watt 600 Watt 680 Watt 700 Watt 13A 14A 14A 17A 8.0 8.8 9.5 10.2 | 600VA 700VA 800VA 900VA 900VA 100-290V 100-290V 100-290V 100-290V 540 Watt 600 Watt 680 Watt 700 Watt 740 Watt 13A 14A 14A 17A 17A 8.0 8.8 9.5 10.2 10.2 |



India's most trusted Home UPS for rural and semi-urban areas with in-built heavy duty charger that charges the battery with full current even at low voltage. It is an ideal choice for areas with low input voltage and power cut duration from 6-12 hours.

Key Features

- Smart charge technology that can charge the battery faster than normal long back-up UPS
- · Charges the battery even at as low as 95 volts of input mains thereby eliminating the need for external stabilizer
- Dual charging current option as per connected battery capacity
- User selectable three mode battery selections for Flat Plate, Tubular & Local Battery



Square wave



24 months warranty



Low voltage charging- 95 volts



MCB protection





| Model | Rhino Charge 1125 | Rhino Charge 1425 | | | | | | | |
|-----------------------------------|--|-------------------|--|--|--|--|--|--|--|
| Capacity | 900VA | 1100VA | | | | | | | |
| Input | | | | | | | | | |
| Voltage Output | 90-290V | 90-290V | | | | | | | |
| | | | | | | | | | |
| Max. Bulb Load Battery | 720 Watt | 780 Watt | | | | | | | |
| Maximum Charging Current Physical | 16A | 20A | | | | | | | |
| Gross Weight (Kg.) | 14.20 | 14.40 | | | | | | | |
| Dimension LxWxH (cm) | 40.2x32x13.2 | 40.2x32x13.2 | | | | | | | |
| Protection | Overload, Short-circuit, Battery Deep Discharge Protection & Battery Reverse Polarity Protection | | | | | | | | |






Luminous Pro UPS with high KVA range has features such as load and battery level display in percentage, MCB protection, seven segment digital display and faster charging ability, making it a preferred Home UPS model.

Key Features

- Battery charge level & load percentage display
- Smart charge technology that can charge battery quicker than normal long back-up UPS
- · Capable of running heavy loads such as laser printers, photo-copiers, scanners, etc
- Charges the battery with full current even when the mains input voltage is as low as 95v
- User selectable switch for battery type (tubular, flat plate & local battery) for optimum battery life & performance



| Model | Pro UPS 2250 |
|--------------------------------------|---|
| Capacity | 2000VA |
| Input | |
| Voltage Output | 100-290V |
| Max. Bulb Load Battery | 1600 Watt |
| Maximum Charging Current Physical | 20A |
| Gross Weight (Kg.) | 20.50 |
| Dimension LxWxH (cm) Protection | 40x33.8x15 Overload, Deep Discharge, Short-circuit, Reverse Polarity & Input Mains Protection Through MCB |



Cruze 2 KVA is a pure sine wave Home UPS. The lower change over time and heavy transformer makes it suitable for running sensitive appliances such as embroidery machine, dental chair, water motors, etc.

Key Features

- · High over-load handling capacity
- Advanced battery management which enhances battery life up to 70%
- · Installation and maintenance friendly
- · No user-action required: Automatic Start



Pure sine wave output



24 months warranty



Synchronized changeover



MCB protection



Seven segment



By pass switch

| Model | 2KVA |
|-----------------------------------|--|
| Capacity | 2000VA/24V |
| Input | |
| Voltage Output | 100-285V |
| Max. Bulb Load Battery | 1600 Watt |
| Maximum Charging Current Physical | 21A |
| Gross Weight (Kg.) | 22.25 |
| Dimension LxWxH (cm) Protection | 28x30.5x28 Overload, short-circuit, Battery deep discharge protection & Battery reverse polarity protection |



Homes and commercial establishments have higher power needs. Also, frequent power cuts can hamper the overall performance of the appliances. Luminous higher KVA offers high quality and reliable power back-up solution for running office and sensitive equipments.

Key Features

- · High over-load handling capacity
- · Installation and maintenance friendly
- Advanced battery management which enhances battery life up to 70%
- · Intelligent battery charging mechanism



Pure sine wave output



24 months warranty



MCB protection



By pass switch



Seven segment display




| - Commodi Opodinodiono | | | | | N | | | | | | |
|-----------------------------------|------------|--|------------|----------------|----------------|--------------|--|--|--|--|--|
| Model | 2.5KVA | 3.5KVA | 5.2KVA | 5.5KVA | 7.5KVA10KVA | | | | | | |
| Capacity | 2500VA/36V | 3500VA/48V | 5200VA/72V | 5500VA/96V | 7500VA/120V 10 | 000VA/180V | | | | | |
| Input | | | | | | | | | | | |
| Voltage Output | 100-285V | 100-285V | 140-280V | 140-280V | 140-280V | 140-280V | | | | | |
| Max. Bulb Load Battery | 2000 Watt | 2800 Watt | 4000 Watt | 4200 Watt | 6000 Watt | 8000 Watt | | | | | |
| Maximum Charging Current Physical | 21A | 21A | 21A | 12A | 12A | 12A | | | | | |
| Gross Weight (Kg.) | 23.00 | 31.90 | 44.50 | 75.20 | 80 | 123.8 | | | | | |
| Dimension LxWxH (cm) | 28X30.5X28 | 28x30.5x38 | 28x36.5x38 | 58.8X34.1X34.7 | 60x35x36 | 62.5x34.5x51 | | | | | |
| Protection | Overloa | Overload, Short-circuit, Battery Deep Discharge Protection & Battery Reverse Polarity Protection | | | | | | | | | |

Comparison Chart

| Model Number | Rating | Sine Wave | Battery System | Max. Charging Current (Amp) | Battery Water Level Indication | MCB Protection | Maximum Bulb Load (watt)# | MRP |
|---------------------|---------|--------------|-------------------|--------------------------------|-----------------------------------|-------------------|------------------------------|--------|
| Electra Square | | | | | | | | |
| Electra Square 665i | 600 VA | | 12V | 13 amp | | | 540 | 6,000 |
| Electra Square 765 | 700 VA | | 12V | 14 amp | | Р | 600 | 6,300 |
| Electra Square 865+ | 800 VA | | 12V | 14 amp | | Р | 680 | 6,760 |
| Electra Square 965 | 875 VA | | 12V | 17 amp | | Р | 700 | 7,300 |
| Electra Square 1065 | 900 VA | | 12V | 17 amp | | Р | 740 | 8,860 |
| Electra Square 1665 | 1500 VA | | 24V | 17 amp | | Р | 1350 | 10,160 |
| Rhino Charge | | | | | | Р | | |
| Rhino Charge 1125 | 900 VA | | 12V | 16 amp | | Р | 720 | 9,500 |
| Rhino Charge 1425 | 1100 VA | | 12V | 20 amp | | Р | 780 | 10,10 |
| Rhino Charge 1725 | 1500 VA | | 24V | 20 amp | | Р | 1200 | 10,60 |
| Electra Sine | | | | | | Р | | |
| Electra Sine 865 | 700 VA | Р | 12V | 14 amp | | Р | 600 | 7,900 |
| Electra Sine 1065 | 900 VA | Р | 12V | 17 amp | | Р | 720 | 10,10 |
| Pro UPS | | | | | | Р | | |
| Pro UPS 2250 | 2000 VA | | 24V | 20 amp | | Р | 1600 | 14,46 |
| Cruze | | | | | | P P | | |
| Cruze 2000 24V | 2 KVA | Р | 24V | 21 amp | | Р | 1600 | 20,000 |
| Cruze 2500 36V | 2.5 KVA | Р | 36V | 21 amp | | P P | 2000 | 23,50 |
| Cruze 3500 48V | 3.5 KVA | P P | 48V | 21 amp | | P | 2800 | 27,50 |
| Cruze 5200 72V | 5.2 KVA | P | 72V | 21 amp | | Р | 4000 | 49,50 |
| Cruze 5500 96V | 5.5 KVA | P P | 96V | 12 amp | | P P | 4200 | 51,99 |
| Cruze 6000 120V | 6 KVA | Р | 120V | 12 amp | | | 4800 | 58,00 |
| Cruze 7500 120V | 7.5 KVA | | 120V | 12 amp | | | 6000 | 65,00 |
| Cruze 10000 180V | 10 KVA | | 180V | 12 amp | | | 8000 | 82,00 |

[&]quot;The maximum peak load that home UPS can take at given point of time before getting into overload zone.









Key Features

- Extra thick plates ensure long life
- Special alloy-very low battery maintenance
- Very good charge acceptance- suitable for frequent power cuts
- · Level indicators enable easy maintenance



Flat plate



21-39 months warranty*



Small size and light weight



Low resistence gives longer back-up on higher load



Easy maintenance with level indicators



Factory charged battery in ready to use condition

| Model | Nominal F | Rated | Dimensi | ons of Cont | ainer | Chargin | g Current (Amp)Electrolyte | Weight | (Kg.) | Water |
|---------|-------------------------|------------------|----------------|---------------|----------------------|----------|---|--------|--------|-----------------------------|
| | Voltage C @ 2 (V) | 7 ₀ C | Length (mm) | Width (mm) | Volur Height(Ltrs | Boost Mo | deTrickle Mode MaxStarting Finishing Min(mm) | Dry | Filled | Level Indicator (No.) |
| LE 3539 | 12 | 135 | 505 | 220 | | | | 27.5 | 41.5 | 6 |
| LE 5539 | 12 | 150 | 505 | 220 | | | 11345425812.8013.606.80 52125810.6015.107.8130 | 29.5 | 44.5 | 6 |



Key Features

- Extremely high purity, corrosion resistant proprietary spine alloy composition ensures longer battery service life
- Tubular plate construction ensures uniform distribution of positive active material for extremely long life and superior performance
- Extra strong, flexible oxidation-resistant gauntlet for higher performance and extremely long life
- Plates specially designed for better charge acceptance



Short tubular battery



24-48 months warranty*



Factory charged battery in ready to use condition



Long & tubular plates give more back-up & longer life



Ideal for longer duration & frequent power cut areas



Easy maintenance with level indicators

| Model | Nominal R | ated | Dimens | ions of Cont | iner Charging Current (Amp)Electrol | lyte Weigl | nţ (Kg.) | Water |
|-----------------------|---------------------------|-----------|----------------|---------------|--|--------------|--------------|-----------------------------|
| | Voltage Ca @ 27 (V) | | Length (mm) | Width (mm) | Volume Boost ModeTrickle Mode Height(Ltrs.) MaxStarting Finis | Dry | Filled | Level Indicator (No.) |
| LET 328 LESTJ 5548 | 12 12 | 80 150 | 410 517 | 174 272 | 10.502858.104.0067.0 269.0 16.6028815.107.60126.0 504.0 | 17.2 34.1 | 29.3 54.6 | 6 |



Key Features

- Extremely high purity, corrosion resistant proprietary spine alloy composition ensures longer battery service life
- Tubular plate construction ensures uniform distribution of positive active material for extremely long life and superior performance
- Extra strong, flexible oxidation-resistant gauntlet for higher performance and extremely long life
- Plates specially designed for better charge acceptance



Tall tubular battery



42-48 months warranty*



Factory charged battery in ready to use condition



Long & tubular plates give more back-up & longer life



High durability with sealed plastic housing



Easy maintenance with level indicators

| Model | Nominal F | ated | Dimens | ions of Cont | U U U U U U U U U U U U U U U U U U U | Weigh | t _, (Kg.) | Water |
|---|--|---|---|--|--|--|--|-----------------------------|
| | Voltage C @ 2 (V) | 7 _° C | Length (mm) | Width (mm) | Volume Boost ModeTrickle Mode Height(Ltrs.) MaxStarting Finishing Min(mm) | Dry | Filled | Level Indicator (No.) |
| LETT 18000 LETT 15036 LE 18036TT LE 578 TT LE 568 TT LE 590 TT LETT 20060 | 12 12 12 12 12 12 12 | 145 150 150 155 155 175 200 | 503 503 503 503 503 503 503 | 189 189 189 189 189 189 | Current Current (mA) (mA) 36218.0014.107.10122.0 487 41118.907.60126.0 50415.10 41121.007.60126.0 50415.10 41121.007.60126.0 50415.10 41121.508.10134.0 53816.10 41121.009.10151.0 60518.10 41121.3010.10168.0 672 | 28.0 28.4 33.0 33.0 31.0 37.0 38.5 | 48.5 52.1 57.0 57.0 56.0 61.0 64.8 | 6 1 6 6 6 6 |

Comparison Chart

| Model Name | Product Rating | Total Warranty (Months) | Replacement Warranty (Months) | Dimensions in mm (LxWxH) | Back up time (in hrs. & minutes⊭) | MRP |
|---------------|-------------------|----------------------------|----------------------------------|-----------------------------|--------------------------------------|--------|
| Flat Plate | | | | | | |
| LE 3539 | 135 AH | 21+18* | 21 | 505x220x258 | 2:10 | 11,790 |
| LE 5539 | 150 AH | 21+18* | 21 | 505x220x258 | 2:50 | 12,550 |
| Short Tubular | | | | | | |
| LET 328 | 80 AH | 24+6* | 24 | 410x174x285 | 1:20 | 8,390 |
| LESTJ 5548 | 150 AH | 30+18* | 30 | 517x272x288 | 3:00 | 14,150 |
| LETT 18000 | 145 AH | 30+12* | 30 | 503x189x362 | 2:25 | 13,470 |
| Tall Tubular | | | | | | |
| LETT 15036 | 150 AH | 18+18* | 18 | 503x189x411 | 3:00 | 14,805 |
| LE 18036TT | 150 AH | 36 | 36 | 503X189X411 | 3:00 | 15,720 |
| LE 578 TT | 155 AH | 36+12* | 36 | 503x189x411 | 3:00 | 16,900 |
| LE 568 TT | 155 AH | 30+12* | 30 | 503x189x411 | 3:05 | 14,910 |
| LE 590 TT | 175 AH | 36+12* | 36 | 503x189x411 | 3:35 | 18,200 |
| LETT 20060 | 200 AH | 36+12* | 36 | 503x189x411 | 3:50 | 18,800 |

^{*}Battery backup time @ 400 Watt standard bulb load.

Disclaimer:
Photographs of the Products shown above are indicative only. Owning to continuous innovation and improvements, actual product may vary in design, description, colors and color combinations from one shown herein.
Care has been taken to ensure that information contained herein is correct and updated from time to time. Luminous Power Technologies Private Limited, however, takes no responsibility of the variations and reserves its right to make changes in the data/details, without any prior intimation or notice.



| Notes | | |
|-------|------|------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |



Notes

| NOTES | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



MSTECHNOLOGIES

Office: Plot No.: 64, HMT Hills Colony, NearbyTulasi Nagar Community Hall, Kukatpally, Hyderabad-72 Telangana.IndiaTel: +91-9010777780, 9603777780 E-mail: mstsaleshyd@gmail.com, Website: www.mstechnologiesups.com









